400001 Standard **ORION** LED Bulkhead Dual Wattage CCT









Orion is our wattage & colour switchable 3-CCT 12 & 16W LED bulkhead fitting. With long life and high lumen output, this bulkhead is ideal for internal and external use, in most domestic and commercial applications.

FEATURES

- 3-CCT: Switch between 3000K/4000K/6500K
- Dual Wattage Switch between 12w and 16w
- 5-Year warranty
- IP65 rated
- · Slimline Design
- Easy to install
- Emergency and microwave sensor options available











AVAILABLE OPTIONS






Emergency

Sensor

Code	Description	Wattage	Colour	Lumens
400001	Orion Bulkhead - Dual Wattage 12/16w – Standard	12/16W	3000, 4000, 6500K	1200/1600lm
100016	Orion Bulkhead POLO Bezel Black	N/A	N/A	N/A
100017	Orion Bulkhead POLO Bezel Chrome	N/A	N/A	N/A

TECHNICAL SPECIFICATION

LED Type/Qty	SMD2835/182
Lumen Efficacy	100lm/w
Colour Temperature	3000K/4000K/6500K selectable
Luminous Flux	1200lm/1600lm
Colour index	Ra>80
Dimming Options Available	Dali-Dimmable
Input Voltage	220-240Vac, 50/60Hz
Driver output Current (max)	660mA
Driver output Voltage	DC17-24V
IP Rating	IP65
Operating Temperature	-10°- +40°C
Lumen Maintenance	L70/B50 @ 50,000hrs
Switching Cycles	>25,000
Power Factor	>0.9
Warranty	5 Years
Beam Angle	105°
Thermal Cutout	No





400001 Standard **ORION** LED Bulkhead Dual Wattage CCT



TECHNICAL SPECIFICATION

Primary Running Current Energy Rating Range This product contains a light source of energy class E Overall Dimensions 320mm Height (mm) 82.5mm Product Weight (Kg) 0.85kg Class Class 2 IK Rating IK08 Origin of Manufacturer China Driver Manufacturer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Overall Dimensions 320mm Height (mm) 82.5mm Product Weight (Kg) 0.85kg Class Class 2 IK Rating IK08 Origin of Manufacturer China Driver Manufacturer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Height (mm) Product Weight (Kg) Class Class 2 IK Rating IK08 Origin of Manufacturer China Driver Manufacturer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Product Weight (Kg) Class Class 2 IK Rating Origin of Manufacturer China Driver Manufacturer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Class 2 IK Rating IK08 Origin of Manufacturer China Driver Manufacturer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
IK Rating IK08 Origin of Manufacturer China Driver Manufactuer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Origin of Manufacturer China Driver Manufactuer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
Driver Manufactuer Performance Lighting EMC Compliant (EN55015) Yes Construction Twist & Lock
EMC Compliant (EN55015) Yes Construction Twist & Lock
Construction Twist & Lock
District Property of the Prope
Primary Material Plastic
Inner Diffusor N/A
Driver Housing Plastic
Standard & Approvals CE, UKCA
Manufactured in Accordance To BS EN 60598-2-1
CE Marked Yes
UKCA Marked Yes
Input Electrical Connections N / E / L
Method of fix Back screw fix or BESA plate mounting
Replaceable (LED only)light source by a professional yes
Replaceable control gear by a professional yes







